



Tuff-Bilt Tractor Model: K-18-44

Designed For Visibility and Agility

The Tuff-Bilt is well suited for cultivation with twenty inches ground clearance and good visibility. The Tuff-Bilt is very maneuverable with a hydrostatic transmission and 84" turn radius.

2016 Tuff-bilt Tractor

Specifications

Three-Point Hitches:	Front & Rear Category 0; Independently Operated Hydraulic Lifts; 700 lbs Capacity Each
Ground Clearance:	20 inches
Turning Radius:	84 inches
Engine:	Kohler Twin 19hp Gasoline (3 year warranty)
Fuel Capacity:	5 Gallons
Transmission:	Variable Speed Danfoss Hydrostatic: Air Cooled
Final Drive:	Heavy Duty: All Gear
Tires:	Rear—8.3 x 24; Front 4.80 x 12
Electrical:	12 Volt
Length:	Overall—115 inches
Wheelbase:	72 inches
Weight:	1300 lbs
Steering:	Ross Gear
Brakes:	Left & Right Band
Wheel Width Adjustment:	Front 38 inches min.; 60 inches max. (2 inch increments) Rear 36 inches min.; 46 inches max. (variable increments)
Frame:	Heavy Duty, tubular steel constructed frame

Tuff-bilt Tractors Manufacturing, Inc.
2801 I Ave
Walthill, NE 68067
(844) 486-3268
info@tuff-bilt.com / www.tuff-bilt.com

Authorized Dealer: John Shenk
Hillside Cultivator Company
911 Disston View Drive
Lititz, Pennsylvania 17543
Phone : (717) 669-3158

Tuff-bilt Tractors Manufacturing, Inc.
Operating as:
Tuff-bilt Tractors
"the little tractor that can"

